


Model **DLV30A/45A/70A series**

**ESD (electrostatic discharge) protection
compliant with IEC61340-5-1**

**0.4 - 7.0 Nm
Lever Start / Push to Start**

***Brushless screwdriver with
wide torque range corresponds to
various fastening work.***

Torque Diagram (for reference)



Torque Adjustment Cover

Torque Adjustment Cover equipped to prevent accidental setting of the torque.

Eco-friendly design

Adoption of green procurement parts, carbon dust free by use of brushless motor. Eco-friendly design by pursued cleanliness

Reduced heat generation

The start-up current of the motor is controlled to reduce unnecessary heat. The new body design exhausts heat efficiently.

New body design


Robust and high durability realized by high strength plastic. The same optional accessories as conventional models (DLV30/45/70 series) can be equipped.

Grounded Bit

Prevents electrostatic breakdown when the bit contacts the workpiece.

Specifications

Specifications

			30 Series			45 Series (High torque)		70 Series (High torque)
			Low Speed	Medium Speed	High Speed	Low Speed	Medium Speed	Low Speed
Model	Bit	Lever Start Push to Start	DLV30A06L-AY : K	DLV30A12L-AY : K	DLV30A20L-AY : K	DLV45A06L-AY : K	DLV45A12L-AY : K	DLV70A06L-AY : K
			DLV30A06P-AY : K	DLV30A12P-AY : K	DLV30A20P-AY : K	DLV45A06P-AY : K	DLV45A12P-AY : K	DLV70A06P-AY : K
Power Source			DEA0151N-AZ or DEA0241N-AZ		DEA0241N-AZ	DEA0151N-AZ or DEA0241N-AZ	DEA0241N-AZ	
Torque adjustment			Stepless					
Torque (Nm)			Low Torque Spring (Standard accessory) 0.40 - 1.60			2.00 - 4.50		3.80 - 7.00
			High Torque Spring (Standard equipped) 1.20 - 3.00					
Free Speed (min ⁻¹)			650	1200	2000	650	1200	650
Power Consumption (W)			44					
Screw Size (mm)	Machine Screw	2.6 - 5.0				4.5 - 6.0		5.0 - 8.0
	Tapping Screw	2.5 - 4.0				4.0 - 5.0		4.5 - 6.0
Bit Type (mm)								
Mass (kg)			0.69			0.84 (with Pistol Grip)		
Standard accessories			• Bit NK35 × 2 × 7 × 75 • Suspension Bail • Low Torque Spring • Connection Cord (DLW9073)			• Bit NK35 × 2 × 7 × 75 • Suspension Bail • Connection Cord (DLW9073) • Pistol Grip (DLW2300ESD)		

Electric Screwdriver

Power Supply

Model	DEA0151N-AZ	DEA0241N-AZ
Input	100 - 240 V AC, 50/60 Hz, 60 W	
Output	40 V DC	
Maximum Rated Power (W)	150	240
Mass (kg)	0.56	0.9

*The power cord is sold separately.
Ask us for the required power cord when ordering.



Optional accessories

Pistol Grip



DLW2300ESD

Torque Adjustment Cover




DLW5203 (30 Series)

Vacuum Pickup



DLP7400

Torque Reaction Arm



Grounded 3-Prong Power Cord

North America



DLW9220

Europe



DLW9240

UK



DLW9250

Connection Cord



DLW9073

Relay Cord (To connect DLW9073 and DLW9073)



DLW9074

Focused on you

NITTO KOHKI CO., LTD.

Web www.nitto-kohki.co.jp/e

Head Office

9-4, Nakaikegami 2-chome, Ohta-ku, Tokyo 146-8555, Japan

Tel : +81-3-3755-1111 Fax : +81-3-3753-8791

E-mail : overseas@nitto-kohki.co.jp

DISTRIBUTED BY

This catalog is printed using environmentally friendly paper and vegetable oil inks.