

# SCALING

# NEEDLE SCALER JET CHISEL

Model **JC-16** Lightweight Type



Model **JEX-24** Universal Type



Model **JEX-28** Heavy-duty Type



Model **JEX-2800A** Low-vibration Type



## Specifications

Model	JC-16	JEX-24	JEX-28	JEX-2800A
Rated Air Pressure	MPa {kgf/cm <sup>2</sup> } 0.59 {6}	0.59 {6}	0.59 {6}	0.63 {6.4}
Air Consumption (No load)	m <sup>3</sup> /min 0.15	0.27	0.35	0.43
Stroke Speed	min <sup>-1</sup> 4,000	4,000	4,500	3,700
Needles to be used	mm 2 OD x 150 (29pcs.)	2 OD x 180 (53pcs.) or 3 OD x 180 (23pcs.)	2 OD x 180 (66pcs.) or 3 OD x 180 (28pcs.) or 4 OD x 180 (14pcs.)	
Hose Size	inch 3/8	3/8	3/8	3/8
Mass (Weight)	kg 1.4	2.7	3.5	3.1

Standard Accessories	JC-16	JEX-24	JEX-28	JEX-2800A
	<ul style="list-style-type: none"> <li>• Needle 2mm OD x 150 mm : 29 pcs. (Needle 2mm OD x 150 mm : 29 pcs. on the body)</li> <li>• Bushing PT3/8 x NPT3/8 : 1 pc.</li> <li>• Hose Nipple PT3/8 x 3/8 : 1 pc.</li> </ul>	<ul style="list-style-type: none"> <li>• Needle 3mm OD x 180 mm : 23 pcs. on the body</li> <li>• 6 mm Hex. Socket Screw Key : 1 pc.</li> <li>• Bushing PT3/8 x NPT3/8 : 1 pc.</li> <li>• Hose Nipple PT3/8 x 3/8 : 1 pc.</li> </ul>	<ul style="list-style-type: none"> <li>• Needle 4mm OD x 180 mm : 14 pcs. (Needle 3mm OD x 180 mm : 28 pcs. on the body)</li> <li>• Needle Supporter 4mm OD : 1pc.</li> <li>• Bushing : 1 pc.</li> <li>• Hose Nipple : 1 pc.</li> </ul>	<ul style="list-style-type: none"> <li>• Needle 4mm OD x 180 mm : 14 pcs. (Needle 3mm OD x 180 mm : 28 pcs. on the body)</li> <li>• Needle Supporter 4mmOD : 1pc.</li> <li>• Bushing : 1 pc.</li> <li>• Hose Nipple : 1 pc.</li> </ul>

## Electric Needle Scaler

Model **EJC-32A**



Standard Accessories	
	<ul style="list-style-type: none"> <li>• Needle 3mm OD x 180 mm : 30 pcs. (15 pcs.)</li> <li>• 6 mm Hex. Socket Screw Key : 1 pc.</li> </ul>

## The same excellent performance as our air tool!

Operated with standard electric supply to households. Special long and slim barrel design suitable for narrow corners. Double-insulated motor does not need grounding. Free subhandle position best fit to your working situation.

## Specifications

Model	EJC-32A	
Power Supply	115 VAC 60Hz	230 VAC 50Hz
Rated Power Consumption	W 300	300
Rated Current	A 2.8	1.4
Rated Duty	minutes 30	
Stroke Speed	min <sup>-1</sup> 3,000	
Needles to be used	mm 2 OD x 180 (32 pcs.) or 3 OD x 180 (15 pcs.)	
Power Cord	m 5	
Mass (Weight)	kg 4.5	

## Optional Needles



PN	Part Name	Q'ty	PN	Part Name	Q'ty	Model
TA98780	Needle 2 mm OD x 150 mm	100 pcs.	TP00338	Needle Supporter 2 mm OD	1 pc.	JT-20,
TA98781	Needle 2 mm OD x 180 mm	100 pcs.	TP00337	Needle Supporter 3 mm OD	1 pc.	JEX-20
TA9A213	Needle 2 mm OD x 300 mm	50 pcs.	TQ05210	Needle Supporter 2 mm OD	1 pc.	AJC-16
TA9A214	Needle 2 mm OD x 500 mm	50 pcs.	TQ04554	Needle Supporter 3 mm OD	1 pc.	
TA98782	Needle 3 mm OD x 180 mm	100 pcs.	TP00290	Needle Supporter 2 mm OD	1 pc.	JC-16
TA9A216	Needle 3 mm OD x 300 mm	50pcs.	TP02244	Needle Supporter 2 mm OD	1 pc.	JEX-24
TA9A217	Needle 3 mm OD x 500 mm	50pcs.	TP02245	Needle Supporter 3 mm OD	1 pc.	
TA9A218	Needle 3 mm OD x 800 mm	50pcs.	TP01499	Needle Supporter 2 mm OD	1 pc.	JEX-28,
TA98783	Needle 4 mm OD x 180 mm	50 pcs.	TP01461	Needle Supporter 3 mm OD	1 pc.	JEX-2800A
TA9A220	Needle 4 mm OD x 300 mm	50 pcs.	TP01462	Needle Supporter 4 mm OD	1 pc.	
TA9A221	Needle 4 mm OD x 500 mm	50 pcs.	TP16475	Needle Supporter 2 mm OD	1 pc.	EJC-32A
			TP16301	Needle Supporter 3 mm OD	1 pc.	